

LP5+
Technical specifications

Functions

Lifting capacity : 250 kg
 Lifting speed : 13 mm/sec

Operation

Electric : Operating panel
 Emergency stop : Electronic
 Emergency lowering : Mechanical
 Safety lists : Mechanical/electrical safety lists

Weight

LP5+ : 150 kg
 Safety gate : 39 kg

Materials

Materials : Aluminium
 Materials : Powder coated/galvanized steel
 Railing : Aluminium and transparent polycarbonate
 Safety gate : Aluminium/steel and transparent polycarbonate
 Cover plate, Safety gate : Water resistant plywood

Measurements

A : 150 - 875 mm
 B : 1100 mm
 C : 1602 mm
 D : 790 mm
 E : 900 mm
 F : 1076 mm
 Max. lifting height without safety gate : 500 mm

Safety gate

G : 900 mm
 H : 1100 mm
 J : 55 mm
 K : 1100 mm

Electrical parts

On/off : Automatically
 Power consumption
 Stand-by : 3 W
 Operation : 14,7 W
 Periodic load : 10/90
 Fuse : T10A
 Batteries : 2 x 12V/4.5 Ah
 Gastight and maintenance-free
 Power supply
 Primary : 230 V/115 V
 Secondary : 24 V DC

Classification, tightness

Components : IP 65
 Operating panel : IP 67
 Safety gate Components : IP 65

**Accessories/
 Miscellaneous**

: Battery package (for temperatures below -10°C)
 Extra operating panels
 Infrared sender and receiver
 Safety gate

Marking

CE-marked according to ISO/DIS 9386-1

EN 60601-1-2
 98/37/EEC

: Power-operated lifting platforms for persons with impaired mobility
 : Medical electrical equipment
 : Approximation of the laws of the Member States on the safety of machines

Item Number/Model

13056-101
 13056-102
 130560
 130565

: LP5+, standard
 : LP5+, for recessing
 : Safety gate, left-hand mounted seen from the platform
 : Safety gate, right-hand mounted seen from the platform

Classification

According to ISO 9999 : 18 30 06

